

LUXPOWER® SERIES 4

390-410W Mono Transparent Backsheet

132 Half-Cell Layout

M6/166mm Cell



Half Cut Cell Technology



MBB Technology



Anti-PID
Low LID
Performance



Less Hot Spot
Shading Effects




Low Power
Temperature Coefficient



Lower BOS & LCOE

Linear performance Warranty



Comprehensive Certificates

- ISO9001:2015 QMS
- ISO14001:2015 EMS
- ISO45001:2018 OHSMS
- IEC61215/IEC61730 Standard quality



LUXEN SOLAR ENERGY CO., LTD.

Suzhou: A301, Zhongyi Building, Suzhou, Jiangsu, 215168, China


Nantong: No.1, Haiyue Road, Nantong, Jiangsu, 226000, China

T: +86 512 6708 1572 | F: +86 512 6708 1570 | sales@luxensolar.com

www.luxensolar.com

MECHANICAL CHARACTERISTICS

Solar Cells	Mono
No. of Cells	132 (6x22)
Dimensions	1925 x 1039 x 35mm
Weight	21.0kgs
Front Glass	3.2mm coated tempered glass
Frame	Anodized aluminium alloy
Junction Box	Ip68 rated (3 by pass diodes)
	4.0mm ²
Output Cables	300mm (+) / 300mm (-)
	Length can be customized
Connectors	Mc4 compatible
Mechanical load test	5400Pa



ELECTRICAL PARAMETERS

POWER CLASS	LNST-390MB	LNST-395MB	LNST-400MB	LNST-405MB	LNST-410MB
	STC	STC	STC	STC	STC
Maximum power (Pmax)	390W	395W	400W	405W	410W
Open Circuit Voltage (Voc)	45.33V	45.56V	45.79V	46.01V	46.23V
Short Circuit Current (Isc)	11.13A	11.19A	11.26A	11.32A	11.39A
Voltage at Maximum power (Vmpp)	36.69V	36.93V	37.17V	37.41V	37.64V
Current Maximum Power (Impp)	10.63A	10.70A	10.76A	10.83A	10.89A
MODULE EFFICIENCY (%)	17.92%	18.15%	18.38%	18.61%	18.84%

STC: Irradiance 1000W/m², cell temperature 25°C, AM1.5G


BIFACIAL OUTPUT-REAR SIDE POWER GAIN

5%	Maximum power (Pmax)	410W	415W	420W	425W	431W
	Module Efficiency STC (%)	20.47%	20.74%	21.00%	21.26%	21.52%
15%	Maximum power (Pmax)	449W	454W	460W	466W	472W
	Module Efficiency STC (%)	22.42%	22.71%	23.00%	23.29%	23.57%
25%	Maximum Power (Pmax)	488W	494W	500W	506W	513W
	Module Efficiency STC (%)	24.37%	24.69%	25.00%	25.31%	25.62%


PACKING CONFIGURATION

Container	20'GP	40'HQ
Pieces per pallet	31	31
Pallets per container	6	24
Pieces per container	186	744

I-V CURVE



LNST-410MB/I-V



OPERATING CHARACTERISTICS

Operating Module Temperature	-40°C to +85°C
Maximum System Voltage	1500 DC (IEC)
Maximum Series Fuse Rating	20A
Power Tolerance	0/+5W

TEMPERATURE CHARACTERISTICS

Nominal Operating Temperature (NMOT)	45±2°C
Temperature Coefficient of Pmax	-0.36%/°C
Temperature Coefficient of Voc	-0.28%/°C
Temperature Coefficient of Isc	+0.05%/°C

Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LUXEN SOLAR have the sole right to make such modification at anytime without further notice.